Norsk Gummi AS

Ruudgata 4
3073 SANDE I VESTFOLD

Telefon: +47 917 35 312

E-post: post@norskgummi.no

CR

CR (Chloroprene Rubber) offers a combination of characteristics that make it the best multifunction rubber. It is ideal for applications involving contact with oils and various chemical products. With excellent resistance to temperature fluctuations, ozone exposure, and weather conditions, it is well-suited for outdoor use. Additionally, CR can be compounded to include flame-retardant properties.

D

Quality rubber solutions.



CR

Wendigo Eco

Quality	CR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,45 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	4 MPa
Elongation at break	200 %
Features	Widely used chloroprene industrial rubber quality with good mechanical properties, fair oil and ozone resistance.
Application	Offshore and industry.

Thickness (mm)	Width (mm)	Length (mm)	Article code
1	1.400	20.000	CR7010 1/0
1,5	1.400	15.000	CR7010 1,5/0
2	1.200	10.000	CR7010 2/0
2	1.400	10.000	CR7010 2/0
3	1.200	10.000	CR7010 3/0
3	1.400	10.000	CR7010 3/0
4	1.200	10.000	CR7010 4/0
4	1.400	10.000	CR7010 4/0
5	1.200	10.000	CR7010 5/0
5	1.400	10.000	CR7010 5/0
6	1.200	10.000	CR7010 6/0
6	1.400	10.000	CR7010 6/0
8	1.200	10.000	CR7010 8/0
8	1.400	5.000	CR7010 8/0
8	1.400	10.000	CR7010 8/0
10	1.000	5.000	CR7010 10/0
10	1.200	5.000	CR7010 10/0
10	1.200	10.000	CR7010 10/0
10	1.400	5.000	CR7010 10/0
10	1.400	10.000	CR7010 10/0
10	1.500	5.000	CR7010 10/0
10	1.500	10.000	CR7010 10/0
10	1.800	5.000	CR7010 10/0
12	1.400	5.000	CR7010 12/0
12	1.400	10.000	CR7010 12/0
15	1.400	5.000	CR7010 15/0
15	1.400	10.000	CR7010 15/0
20	1.400	5.000	CR7010 20/0
20	1.400	10.000	CR7010 20/0
25	1.400	5.000	CR7010 25/0



CR

Wendigo Eco with insertion(s)

Quality	CR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,45 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	4 MPa
Elongation at break	200 %
Features	Widely used chloroprene industrial rubber quality with good mechanical properties, fair oil and ozone resistance.
Application	Offshore and industry.

Thickness (mm)	Insertion(s)	Insertion type	Width (mm)	Length (mm)	Article code
1,5	1	nylon	1.400	10.000	CR7011 1,5/1
1,5	1	nylon	1.400	15.000	CR7011 1,5/1
2	1	nylon	1.200	10.000	CR7011 2/1
2	1	nylon	1.400	10.000	CR7011 2/1
3	1	nylon	1.200	10.000	CR7011 3/1
3	1	nylon	1.400	10.000	CR7011 3/1
3	2	nylon	1.200	10.000	CR7012 3/2
3	2	nylon	1.400	10.000	CR7012 3/2
4	1	nylon	1.200	10.000	CR7011 4/1
4	1	nylon	1.400	10.000	CR7011 4/1
4	2	nylon	1.200	10.000	CR7012 4/2
4	2	nylon	1.400	10.000	CR7012 4/2
5	1	nylon	1.200	10.000	CR7011 5/1
5	1	nylon	1.400	10.000	CR7011 5/1
5	2	nylon	1.400	10.000	CR7012 5/2
6	2	nylon	1.400	10.000	CR7012 6/2
8	2	nylon	1.400	5.000	CR7012 8/2
10	2	nylon	1.200	10.000	CR7012 10/2
10	2	nylon	1.400	5.000	CR7012 10/2
10	2	nylon	1.400	10.000	CR7012 10/2



CR

Wendigo Eco Flat sheets

Quality	CR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,45 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	4 MPa
Elongation at break	200 %
Features	Widely used chloroprene industrial rubber quality with good mechanical properties, fair oil and ozone resistance.
Application	Offshore and industry.

Thickness (mm)	Width (mm)	Length (mm)	Article code
10	1.000	1.000	CR7010 10/0-1x1
15	1.000	1.000	CR7010 15/0-1x1
20	1.000	1.000	CR7010 20/0-1x1
20	1.400	2.000	CR7010 20/0
25	1.000	1.000	CR7010 25/0-1x1
30	1.400	2.000	CR7010 30/0
40	1.400	2.000	CR7010 40/0
50	1.400	2.000	CR7010 50/0



CR

Wendigo Medium

Quality	CR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-25 °C to +80 °C
Specific gravity	1,45 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	5 MPa
Elongation at break	225 %
Features	Widely used chloroprene industrial rubber quality with good mechanical properties, moderate oil and ozone resistance.
Application	Offshore and industry.

Thickness (mm)	Width (mm)	Length (mm)	Article code
1	1.400	20.000	NE70140 1/0
1,5	1.400	15.000	NE70140 1,5/0
2	1.400	10.000	NE70140 2/0
3	1.400	10.000	NE70140 3/0
4	1.400	10.000	NE70140 4/0
5	1.400	10.000	NE70140 5/0
6	1.400	10.000	NE70140 6/0
8	1.400	5.000	NE70140 8/0
8	1.400	10.000	NE70140 8/0
10	1.400	5.000	NE70140 10/0
10	1.400	10.000	NE70140 10/0



CR

Wendigo Premium

Quality	CR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +120 °C C
Specific gravity	1,4 g/cm³
Hardness	65 Shore A ± 5
Tensile strength	10 MPa
Elongation at break	400 %

Features Excellent chloroprene industrial rubber quality with good resistance to heat, ozone, weathering and oil. It has good adhesion to metal and flame retardant properties.

Application Offshore and industry.

Thickness (mm)	Width (mm)	Length (mm)	Article code
1	1.400	20.000	NE65140 1/0
2	1.400	10.000	NE65140 2/0
3	1.400	10.000	NE65140 3/0
4	1.400	10.000	NE65140 4/0
5	1.400	10.000	NE65140 5/0
6	1.400	10.000	NE65140 6/0
8	1.400	5.000	NE65140 8/0
8	1.400	10.000	NE65140 8/0
10	1.400	5.000	NE65140 10/0
10	1.400	10.000	NE65140 10/0



CR

Wendigo 50

Quality	CR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,45 g/cm³
Hardness	50 Shore A ± 5
Tensile strength	4 MPa
Elongation at break	200 %
Features	Widely used chloroprene industrial rubber quality with good mechanical properties, moderate oil and ozone resistance.
Application	Offshore and industry.

Thickness (mm)	Width (mm)	Length (mm)	Article code
1	1.400	20.000	CR5010 1/0
2	1.400	10.000	CR5010 2/0
2,5	1.400	10.000	CR5010 2,5/0
3	1.400	10.000	CR5010 3/0
4	1.400	10.000	CR5010 4/0
5	1.400	10.000	CR5010 5/0
6	1.400	10.000	CR5010 6/0
8	1.400	5.000	CR5010 8/0
10	1.400	5.000	CR5010 10/0
10	1.400	10.000	CR5010 10/0
15	1.400	5.000	CR5010 15/0
15	1.400	10.000	CR5010 15/0
20	1.400	5.000	CR5010 20/0
20	1.400	10.000	CR5010 20/0