Norsk Gummi AS

Ruudgata 4
3073 SANDE I VESTFOLD

Telefon: +47 917 35 312

E-post: post@norskgummi.no

NBR

NBR (Nitrile Butadiene Rubber) offers excellent overall resistance to oil, along with key mechanical properties such as high tensile strength, flexibility, low compression set, and good gas impermeability. It also provides good adhesion to metal and shows moderate aging characteristics. Additionally, it resists inorganic chemical products, except antioxidant agents and chlorine. However, it should not be exposed to ozone, sunlight, or other weather conditions.

B

Quality rubber solutions.



NBR

Satyr Eco

Quality	NBR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,45 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	4 MPa
Elongation at break	200 %
Features	Widely used oil and grease resistant industrial rubber quality with good mechanical properties.
Application	Chemical industries, garages, workshops, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
1	1.400	20.000	NB7010 1/0
1,5	1.400	15.000	NB7010 1,5/0
2	1.200	10.000	NB7010 2/0
2	1.400	10.000	NB7010 2/0
3	1.200	10.000	NB7010 3/0
3	1.400	10.000	NB7010 3/0
4	1.200	10.000	NB7010 4/0
4	1.400	10.000	NB7010 4/0
5	1.200	10.000	NB7010 5/0
5	1.400	10.000	NB7010 5/0
6	1.200	10.000	NB7010 6/0
6	1.400	10.000	NB7010 6/0
8	1.200	10.000	NB7010 8/0
8	1.400	5.000	NB7010 8/0
8	1.400	10.000	NB7010 8/0
10	1.000	5.000	NB7010 10/0
10	1.200	5.000	NB7010 10/0
10	1.200	10.000	NB7010 10/0
10	1.400	5.000	NB7010 10/0
10	1.400	10.000	NB7010 10/0
10	1.500	5.000	NB7010 10/0
10	1.500	10.000	NB7010 10/0
10	1.800	5.000	NB7010 10/0
12	1.400	5.000	NB7010 12/0
12	1.400	10.000	NB7010 12/0
15	1.400	5.000	NB7010 15/0
15	1.400	10.000	NB7010 15/0
20	1.400	5.000	NB7010 20/0
20	1.400	10.000	NB7010 20/0
25	1.400	5.000	NB7010 25/0



NBR

Satyr Eco with insertion(s)

Quality	NBR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,45 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	4 MPa
Elongation at break	200 %
Features	Widely used oil and grease resistant industrial rubber quality with good mechanical properties.
Application	Chemical industries, garages, workshops, etc.

Thickness (mm)	Insertion(s)	Insertion type	Width (mm)	Length (mm)	Article code
1,5	1	nylon	1.400	10.000	NB7011 1,5/1
1,5	1	nylon	1.400	15.000	NB7011 1,5/1
2	1	nylon	1.200	10.000	NB7011 2/1
2	1	nylon	1.400	10.000	NB7011 2/1
3	1	nylon	1.200	10.000	NB7011 3/1
3	1	nylon	1.400	10.000	NB7011 3/1
3	2	nylon	1.200	10.000	NB7012 3/2
3	2	nylon	1.400	10.000	NB7012 3/2
4	1	nylon	1.200	10.000	NB7011 4/1
4	1	nylon	1.400	10.000	NB7011 4/1
4	2	nylon	1.200	10.000	NB7012 4/2
4	2	nylon	1.400	10.000	NB7012 4/2
5	1	nylon	1.200	10.000	NB7011 5/1
5	1	nylon	1.400	10.000	NB7011 5/1
5	2	nylon	1.400	10.000	NB7012 5/2
6	2	nylon	1.400	10.000	NB7012 6/2
8	2	nylon	1.400	5.000	NB7012 8/2
10	2	nylon	1.200	10.000	NB7012 10/2
10	2	nylon	1.400	5.000	NB7012 10/2
10	2	nylon	1.400	10.000	NB7012 10/2



NBR

Satyr Eco flat sheets

Quality	NBR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,45 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	4 MPa
Elongation at break	200 %
Features	Widely used oil and grease resistant industrial rubber quality with good mechanical properties.
Application	Chemical industries, garages, workshops, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
10	1.000	1.000	NB7010 10/0-1x1
15	1.000	1.000	NB7010 15/0-1x1
20	1.000	1.000	NB7010 20/0-1x1
20	1.400	2.000	NB7010 20/0
25	1.000	1.000	NB7010 25/0-1x1
30	1.400	2.000	NB7010 30/0
40	1.400	2.000	NB7010 40/0
50	1.400	2.000	NB7010 50/0



NBR

Satyr Medium

Quality	NBR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +90 °C
Specific gravity	1,45 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	5 MPa
Elongation at break	250 %
Features	Widely used natural oil and grease resistant industrial rubber quality with good mechanical properties. Resistant to propane, natural gas and coal gas.
Application	Chemical industries, garages, workshops, etc.

Thickness (mm)	Insertion(s)	Insertion type	Width (mm)	Length (mm)	Article code
1	0	-	1.200	20.000	NB70140 1/0
1	0	-	1.400	20.000	NB70140 1/0
1,5	0	-	1.400	15.000	NB70140 1,5/0
2	0	-	1.200	10.000	NB70140 2/0
2	0	-	1.400	10.000	NB70140 2/0
2	1	nylon	1.400	10.000	NB70141 2/1
3	0	-	1.200	10.000	NB70140 3/0
3	0	-	1.400	10.000	NB70140 3/0
3	1	nylon	1.400	10.000	NB70141 3/1
3	2	nylon	1.400	10.000	NB70142 3/2
4	0	-	1.200	10.000	NB70140 4/0
4	0	-	1.400	10.000	NB70140 4/0
4	2	nylon	1.400	10.000	NB70142 4/2
5	0	-	1.200	10.000	NB70140 5/0
5	0	-	1.400	10.000	NB70140 5/0
5	2	nylon	1.400	10.000	NB70142 5/2
6	0	-	1.400	10.000	NB70140 6/0
8	0	-	1.400	5.000	NB70140 8/0
8	0	-	1.400	10.000	NB70140 8/0
10	0	-	1.400	5.000	NB70140 10/0
10	0	-	1.400	10	NB70140 10/0



NBR

Satyr Premium

Quality	NBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +110 °C
Specific gravity	1,35 g/cm³
Hardness	65 Shore A ± 5
Tensile strength	10 MPa
Elongation at break	350 %
Features	Excellent natural oil and grease resistant industrial rubber quality with good mechanical properties. Resistant to oil, super, pentane and bio-diesel.
Application	Chemical industries, garages, workshops, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
0,5	1.400	20.000	NB65130 0,5/0
1	1.400	20.000	NB65130 1/0
1,5	1.400	15.000	NB65130 1,5/0
2	1.400	10.000	NB65130 2/0
3	1.400	10.000	NB65130 3/0
4	1.400	10.000	NB65130 4/0
5	1.400	10.000	NB65130 5/0
6	1.400	10.000	NB65130 6/0
8	1.400	5.000	NB65130 8/0
8	1.400	10.000	NB65130 8/0
10	1.400	5.000	NB65130 10/0
10	1.400	10.000	NB65130 10/0



NBR

Satyr Premium 80

Quality	NBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +110 °C
Specific gravity	1,35 g/cm³
Hardness	80 Shore A ± 5
Tensile strength	10 MPa
Elongation at break	350 %
Features	Excellent natural oil and grease resistant industrial rubber quality with good mechanical properties. Resistant to oil, super, pentane and bio-diesel.
Application	Chemical industries, garages, workshops, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
2	1.400	10.000	NB80130 2/0
3	1.400	10.000	NB80130 3/0
4	1.400	10.000	NB80130 4/0



NBR

Satyr 50

Quality	NBR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,45 g/cm³
Hardness	50 Shore A ± 5
Tensile strength	4 MPa
Elongation at break	200 %
Features	Widely used oil and grease resistant industrial rubber quality with good mechanical properties.
Application	Chemical industries, garages, workshops, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
1	1.400	20.000	NB5010 1/0
2	1.400	10.000	NB5010 2/0
2,5	1.400	10.000	NB5010 2,5/0
3	1.400	10.000	NB5010 3/0
4	1.400	10.000	NB5010 4/0
5	1.400	10.000	NB5010 5/0
6	1.400	10.000	NB5010 6/0
8	1.400	5.000	NB5010 8/0
10	1.400	5.000	NB5010 10/0
10	1.400	10.000	NB5010 10/0
15	1.400	5.000	NB5010 15/0
15	1.400	10.000	NB5010 15/0
20	1.400	5.000	NB5010 20/0
20	1.400	10.000	NB5010 20/0

