Norsk Gummi AS

Ruudgata 4
3073 SANDE I VESTFOLD

Telefon: +47 917 35 312

E-post: post@norskgummi.no

SBR

SBR (Styrene Butadiene Rubber) is a widely used standard rubber, known for its excellent mechanical properties. It is well-suited for applications involving wear and impact, with good resistance to abrasion. Its durability makes it a popular choice in the mining industry and various other industrial sectors.

A

Quality rubber solutions.



SBR

Black Miami

Quality	NR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,5 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	3 MPa
Elongation at break	200 %
Features	Widely used industrial rubber quality with good mechanical properties, abrasion and shock resistance.
Application	General purpose gaskets, shock absorption, conveyor belts, insulation, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
1	1.400	10.000	SX70150 1/0
1	1.400	20.000	SX70150 1/0
1,5	1.400	15.000	SX70150 1,5/0
1,5	1.500	15.000	SX70150 1,5/0
1,5	1.500	20.000	SX70150 1,5/0
2	1.200	10.000	SX70150 2/0
2	1.400	10.000	SX70150 2/0
2	1.400	20.000	SX70150 2/0
3	1.200	10.000	SX70150 3/0
3	1.400	10.000	SX70150 3/0
3	1.400	20.000	SX70150 3/0
3	1.800	10.000	SX70150 3/0
4	1.200	10.000	SX70150 4/0
4	1.400	10.000	SX70150 4/0
5	1.200	10.000	SX70150 5/0
5	1.400	10.000	SX70150 5/0
6	1.200	10.000	SX70150 6/0
6	1.400	10.000	SX70150 6/0
8	1.200	10.000	SX70150 8/0
8	1.400	5.000	SX70150 8/0
8	1.400	10.000	SX70150 8/0

(more sizes on the next page)



SBR

Black Miami

Quality	NR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,5 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	3 MPa
Elongation at break	200 %
Features	Widely used industrial rubber quality with good mechanical properties, abrasion and shock resistance.
Application	General purpose gaskets, shock absorption, conveyor belts, insulation, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
10	1.200	5.000	SX70150 10/0
10	1.200	10.000	SX70150 10/0
10	1.400	5.000	SX70150 10/0
10	1.400	10.000	SX70150 10/0
10	1.400	20.000	SX70150 10/0
10	1.800	5.000	SX70150 10/0
12	1.400	5.000	SX70150 12/0
12	1.400	10.000	SX70150 12/0
15	1.400	5.000	SX70150 15/0
15	1.400	10.000	SX70150 15/0
20	1.400	5.000	SX70150 20/0
20	1.400	10.000	SX70150 20/0
25	1.400	5.000	SX70150 25/0
30	1.400	5.000	SX70150 30/0



SBR

Black Miami with insertion(s)

Quality	NR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,5 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	3 MPa
Elongation at break	200 %

Features Widely used industrial rubber quality with good mechanical properties, abrasion and shock resistance.

Application General purpose gaskets, shock absorption, conveyor belts, insulation, etc.

Thickness (mm)	Insertion(s)	Insertion type	Width (mm)	Length (mm)	Article code
1,5	1	cotton	1.400	15.000	SX70151 1,5/1
2	1	cotton	1.400	10.000	SX70151 2/1
2	1	cotton	1.200	10.000	SX70151 2/1
3	1	cotton	1.200	10.000	SX70151 3/1
3	1	cotton	1.400	10.000	SX70151 3/1
3	1	cotton	1.500	10.000	SX70151 3/1
3	2	cotton	1.200	10.000	SX70152 3/2
3	2	cotton	1.400	10.000	SX70152 3/2
4	1	cotton	1.200	10.000	SX70151 4/1
4	1	cotton	1.400	10.000	SX70151 4/1
4	2	cotton	1.200	10.000	SX70152 4/2
4	2	cotton	1.400	10.000	SX70152 4/2
5	1	cotton	1.200	10.000	SX70151 5/1
5	1	cotton	1.400	10.000	SX70151 5/1
5	1	cotton	1.500	10.000	SX70151 5/1
5	2	cotton	1.200	10.000	SX70152 5/2
5	2	cotton	1.400	10.000	SX70152 5/2

(more sizes on the next page)



SBR

Black Miami with insertion(s)

Quality	NR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,5 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	3 MPa
Elongation at break	200 %
Features	Widely used industrial rubber quality with good mechanical properties, abrasion and shock resistance.
Application	General purpose gaskets, shock absorption, conveyor belts, insulation, etc.

Thickness (mm)	Insertion(s)	Insertion type	Width (mm)	Length (mm)	Article code
6	1	cotton	1.200	10.000	SX70151 6/1
6	1	cotton	1.400	10.000	SX70151 6/1
6	2	cotton	1.200	10.000	SX70152 6/2
6	2	cotton	1.400	10.000	SX70152 6/2
8	2	cotton	1.200	5.000	SX70152 8/2
8	2	cotton	1.200	10.000	SX70152 8/2
8	2	cotton	1.400	5.000	SX70152 8/2
8	2	cotton	1.400	10.000	SX70152 8/2
8	2	cotton	1.500	5.000	SX70152 8/2
10	2	cotton	1.200	10.000	SX70152 10/2
10	2	cotton	1.400	5.000	SX70152 10/2
10	2	cotton	1.500	10.000	SX70152 10/2
15	3	cotton	1.400	5.000	SX70153 15/3



SBR

Black Miami flat sheets

Quality	NR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,5 g/cm³
Hardness	70 Shore A ± 5
Tensile strength	3 MPa
Elongation at break	200 %
Features	Widely used industrial rubber quality with good mechanical properties, abrasion and shock resistance.
Application	General purpose gaskets, shock absorption, conveyor belts, insulation, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
10	1.000	1.000	SX70150 10/0-1x1
15	1.000	1.000	SX70150 15/0-1x1
20	1.000	1.000	SX70150 20/0-1x1
25	1.000	1.000	SX70150 25/0-1x1
30	1.000	1.000	SX70150 30/0-1x1
40	1.000	1.000	SX70150 40/0-1x1
50	1.000	1.000	SX70150 50/0-1x1



SBR

Zenstar

Quality	NR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,3 g/cm³
Hardness	65 Shore A ± 5
Tensile strength	7 MPa
Elongation at break	300 %
Abrasion	250 mm³
Features	Widely used industrial rubber quality with good mechanical properties, abrasion and shock resistance.
Application	General purpose gaskets, shock absorption, conveyor belts, insulation, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
1	1.400	20.000	SB65130 1/0
1,5	1.400	15.000	SB65130 1,5/0
2	1.400	10.000	SB65130 2/0
3	1.400	10.000	SB65130 3/0
4	1.400	10.000	SB65130 4/0
5	1.400	10.000	SB65130 5/0
6	1.400	10.000	SB65130 6/0
6	1.400	20.000	SB65130 6/0
8	1.400	10.000	SB65130 8/0
8	1.400	20.000	SB65130 8/0
10	1.400	10.000	SB65130 10/0
10	1.400	20.000	SB65130 10/0
12	1.400	10.000	SB65130 12/0
15	1.400	10.000	SB65130 15/0

Zenstar with EP ply

Thickness (mm)	Insertion(s)	Insertion type	Width (mm)	Length (mm)	Article code
4	1	EP	1.500	10.000	SB65131 4/1EP
6	2	EP	1.500	10.000	SB65132 6/2EP



SBR

Black Miami 50

Quality	NR/SBR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +70 °C
Specific gravity	1,5 g/cm³
Hardness	50 Shore A ± 5
Tensile strength	3 MPa
Elongation at break	200 %
Features	Widely used industrial rubber quality with good mechanical properties, abrasion and shock resistance.
Application	General purpose gaskets, shock absorption, conveyor belts, insulation, etc.

Thickness (mm)	Width (mm)	Length (mm)	Article code
2	1.400	10.000	SX50150 2/0
3	1.400	10.000	SX50150 3/0
4	1.400	10.000	SX50150 4/0
5	1.400	10.000	SX50150 5/0
6	1.400	10.000	SX50150 6/0
8	1.400	5.000	SX50150 8/0
8	1.400	10.000	SX50150 8/0
10	1.400	5.000	SX50150 10/0
10	1.400	10.000	SX50150 10/0
15	1.400	5.000	SX50150 15/0
20	1.400	5.000	SX50150 20/0