Norsk Gummi AS

Ruudgata 4
3073 SANDE I VESTFOLD

Telefon: +47 917 35 312

E-post: post@norskgummi.no

Various

H

Quality rubber solutions.



Various

Kabira Neobenzid

Quality	NBR/PVC
Colour	Green
Surface	Both sides smooth finish
Temperature range	-30 °C to +110 °C
Specific gravity	1,45 g/cm³
Hardness	65 Shore A ± 5
Tensile strength	6,5 MPa
Elongation at break	320 %
Features	Good resistance to oils and strong mechanical properties. No gas permeability. Moderate aging properties.
Application	Petrochemical industries, garages, workshops.

Thickness (mm)	Width (mm)	Length (mm)	Article code
2	1.400	10.000	NB65145G 2/0
3	1.400	10.000	NB65145G 3/0
4	1.400	10.000	NB65145G 4/0
5	1.400	10.000	NB65145G 5/0
6	1.400	10.000	NB65145G 6/0
10	1.400	5.000	NB65145G 10/0



Various

Serra CSM

Quality	CSM
Colour	Black
Surface	Both sides smooth finish
Temperature range	-30 °C to +130 °C
Specific gravity	1,40 g/cm³
Hardness	65 Shore A ± 5
Tensile strength	10 MPa
Elongation at break	350 %
Features	Exceptional resistance to ozone, weathering, chemicals, and heat. Good mechanical strength, flexibility, and flame resistance. High durability in harsh environments.
Application	Automotive, mining, marine and aeronautical industries.

Thickness (mm)	Width (mm)	Length (mm)	Article code
2	1.400	10.000	HN65140 2/0
3	1.400	10.000	HN65140 3/0
4	1.400	10.000	HN65140 4/0
5	1.400	10.000	HN65140 5/0
6	1.400	10.000	HN65140 6/0

For more specialised rubber solutions visit **ZenithEurope.com**



Various

Rama Butyl

Quality	IR
Colour	Black
Surface	Both sides smooth finish
Temperature range	-45 °C to +120 °C
Specific gravity	1,20 g/cm³
Hardness	60 Shore A ± 5
Tensile strength	9 MPa
Elongation at break	350 %
Features	Very low permeability to air and other gases. Excellent resistance to ozone, oxidation, and sunlight. Wide temperature range.
Application	Pharmaceutical, construction and automotive industries.

Thickness (mm)	Width (mm)	Length (mm)	Article code
2	1.400	10.000	IR60120 2/0
3	1.400	10.000	IR60120 3/0
4	1.400	10.000	IR60120 4/0
5	1.400	10.000	IR60120 5/0
6	1.400	10.000	IR60120 6/0